# Dunk 1



**Scale 1:500** 

# Wellsite Lithology Log

### **Well Data**

Dunk 1 Well Name: Status: Exploration Area: Surat (8743) Basin: Bowen Basin ATP 645 Location:

UWI: 100000789132

Partners:

BNG (Surat) Pty Ltd

100%

TCL 1, EWE106 Rigs: 27° 04' 04.3781" S Latitude: 149° 25' 30.8309" E Longitude: Spud Date: 20-09-2014 (TCL 1)

TD Date: 27-12-2014 (EWE 106) 15-01-2015 (EWE 106) Rig Release:

Mean Sea Level

295.71m **RT Elevation:** GL Elevation: 286.94m

**TD Formation:** Combarngo Volcanics 3180.00mMDRT TD Depth:

Remarks:

Datum:

**Geologists** 


Operations Geologist: Anthony Mountford Wellsite Geologist: Anthony Drake Wellsite Geologist: Jim Mitchell Wellsite Geologist: Brendan Lacy Wellsite Geologist: John Pitman

**Contractors** 

Drilling: Easternwell Energy Wireline Logging: Schlumberger Cementing: Halliburton Mud Engineering: Newpark Mud Logging: Weatherford MWD: Pathfinder Coring: Halliburton


Hole and Casing						
Bit Size (inch)	Depth (m)	Casing Size (inch)	Shoe Depth (m)			
26"	68.61	20"	64.91			
17 1/2"	1106.38	13 3/8"	1101.04			
12 1/4"	2330.00	9 5/8"	2326.84			
6 3/4"	3180.00	4 1/2"	3178.00			

#### **Location Map**




06-12-2014

2330.00



**Well Structure** 





#### **Events and Remarks**

<u>Date</u>	Depth (mMDRT)	<u>Details</u>
24-09-2014		TCL 1 moved onto location and commence rig up
25-09-2014		Continue rig up
26-09-2014		Complete rig up and spud well.
27-09-2014		Continue to drill ahead to section TD. Rig up and run conductor casing.
28-09-2014		Continue to run casing. Cement casing. Rig release.
20-11-2014	68.61	Spudded Dunk 1 at 17:30 hours on the 20-11-2014 and drilled 17 1/2" Surface hole to 66.40m MDRT.
21-11-2014	75.30	Drilled 17 1/2" surface hole from 66.40 to 75.30m MDRT. POOH. Made up 17 1/2" rotary BHA with Pathfinder LWD/MWD tools. RIH to shoe, performed flow rate test. Max flow 450 gpm. Made repairs to mud ta
22-11-2014	127.00	Completed repairs on mud tanks. RIH and drilled 17 1/2" surface hole to 127.00m MDRT.
23-11-2014	402.00	Drilled 17 1/2" surface hole to 402.00m MDRT.
24-11-2014	995.00	Drilled 17 1/2" surface hole to 995m MDRT.
25-11-2014	1106.38	Drilled 17 1/2" surface hole to 1106.38m MDRT. Conducted Wiper Trip.
26-11-2014	1106.38	POOH to surface. Broke out BHA and laid down MWD. Rigged up to run 13 3/8" casing.
27-11-2014	1106.38	Ran in hole with 13 3/8" casing to target depth. Landed casing. Rigged down CRT and rigged up cement head. Broke circulation and conditioned mud. Cemented casing as per programme.
28-11-2014	1106.38	Displaced cement as per programme. Pressure tested casing. WOC. Nippled down bell nipple and riser. Cut and dressed casing. Nippled up well head.
29-11-2014	1106.38	Nippled up well head. Nippled up BOP and pressure tested.
30-11-2014	1106.38	Pressure tested BOP. Installed wear bushing. Made up 12 ¼" BHA and RIH to ~ 250m MDRT.
01-12-2014	1106.38	Slip and cut drilling line. Continued to RIH with the 121/4" BHA picking up singles. Circulated and conditioned mud. Conducted stripping drill. Drilled out shoe track.
02-12-2014	1328.50	Drilled out shoe track and new formation to 1110.63m MDRT & circulated, displacing well to new drilling fluid. Rigged up & performed XLOT. EMW=19.3ppg. Drilled 121/4" hole to 1328.50m MDRT
03-12-2014	1687.00	Drilled ahead 12 ¼" hole section from 1328.50m to 1687.00m MDRT
04-12-2014	1994.00	Drilled ahead 12 ¼" hole section from 1687.00m to 1871.5m MDRT. Repaired leak in bell nipple. Resumed drilling to 1994m MDRT.
05-12-2014	2240.00	Drilled ahead 12 1/4" hole section from 1994.00m to 2240.00m MDRT.


Drilled ahead 12 ¼" hole section from 2240.00m to 2330.00m MDRT. Circulated. POOH to casing shoe. Slipped and cut drill line. RIH to 1986m MDRT.


07-12-2014	2330.00	Continued to RIH to section TD. Circulated hole. POOH to su	rface. Laid down BHA. Rigged ι	ıp for wireline logging. RIH wi	th wireline logging tools.				
08-12-2014	2330.00	Continued to RIH with wireline logging tools from ~400m to 1: Schlumberger wire line.							
09-12-2014	2330.00	<del>-</del>	Ran 9 5/8" casing as per programme. No hole issues observed. Total of 174 joints of casing run. Circulated 2 x open hole volumes while reciprocating casing. Picked up casing hanger.						
10-12-2014	2330.00	Landed out 9 5/8" casing hanger in well head with 9 5/8" casing shoe set at 2326.84 mRT. Circulated 2 x open hole volumes. Held PJSM, cemented casing as per Halliburton programme. Install BOP's.							
11-12-2014	2330.00	Pressure tested wellhead and BOP's.							
12-12-2014	2330.00	Made up 6 3/4" MWD/LWD rotary BHA. Function tested tools on 5 1/2" DP from mast.	Made up 6 3/4" MWD/LWD rotary BHA. Function tested tools. RIH picking up 4 3/4" DC's, 4" HWDP and 4" DP from racks. Continued to run in the hole						
13-12-2014	2370.00	Drilled out shoe and 5m of new formation. Conducted XLOT.	Drilled 6 3/4" production hole fr	om 2335m to 2370m MDRT.					
14-12-2014	2555.00	Drilled 6 3/4" production hole from 2370m to 2555m MDRT. O	Conducted Wiper Trp to 2259m I	MDRT.					
15-12-2014	2703.00	Drilled 6 3/4" production hole from 2555m to 2703m MDRT.							
16-12-2014	2870.00	Drilled 6 3/4" production hole from 2703m to 2870m MDRT. (	Core Point). Circulated hole clea	an.					
17-12-2014	2870.00	Wiper Tripped. 2870m-2308m. RIH to 2857m, Washed to 287 casing shoe. Continued to POOH to 342mRT.	70m. Circulate hole clean. POOl	Hogging up GR-Resistivity in	memory mode from 2870m to				
18-12-2014	2870.00	POOH 6 3/4" BHA from 342 mRT to surface. Made up and R 2737-2400m & 2561-2752m. Washed down from 2752-2767r		" coring assembly. Worked the	rough tight spots from				
19-12-2014	2893.00	Cored 6 3/4" hole from 2870m to 2893m MDRT.							
20-12-2014	2897.00	Cored 6 3/4" hole from 2893m to 2897m MDRT. Pulled out of	the hole and recovered core 1.	Recovered 26.66m (98.7% re	covery)				
21-12-2014	2924.27	Cored 6 3/4" hole from 2897m to 2924.27m MDRT. Pulled ou	t of the hole with core to 1182m	MDRT.					
22-12-2014	2924.27	Pulled out of the hole with core from to 1182m MDRT to surfacored section to 2882m MDRT.	ace. Recovered Core 2. 27.27m	(100%). Made up 6 3/4" drillin	g BHA and RIH & logged				
23-12-2014	3030.47	Continued logging cored section from 2882m to 2924.27 MDI							
24-12-2014	3059.55	Drilled ahead 6 3/4" hole from 3030.47m MDRT to 3059.55m	· ·	,	· · · · · · · · · · · · · · · · · · ·				
25-12-2014	3082.50	Made up 6 3/4" BHA with MWD/LWD Motor. Ran in hole and	directional drill ahead 6 3/4" hole	e from 3059.55m to 3082.50n	n MDRT.				
26-12-2014	3155.00	Drilled 6 3/4" BHA with MWD/LWD Motor from 3082.50m to 3	3155.00m MDRT.						
27-12-2014	3180.00	Continued to drill ahead 6 $\%$ " hole from 3155m to 3180m MD wireline loggers rig up Run 1.	· ,		·				
28-12-2014	3180.00	Riged up and ran wireline logging Run 1. Rigged down Run for Run 3.							
29-12-2014	3180.00	Continued to RIH with logging Run 3. Tagged bottom and logged up. POOH and rigged down Run 3 tools. Safety meeting and rigged up for wireline Ru 4. Ran wireline log Run 4.							
30-12-2014	3180.00	Continued logging Run 4. Pulled out of hole with Run 4 tool string. Rigged down loggers and prepared for wiper trip. Picked & made up BHA and RIH. Circulated hole clean. Slipped and cut drill line.							
31-12-2014	3180.00	Pulled out of hole with wiper assembly. Laid down BHA. Rigged up and ran wireline logging Run 5 (MSCT). Tool failed. Pulled out of hole. Ran in with replacement tool and resumed MSCT(Run 6).							
01-01-2015	3180.00	Continued logging run 6 - MSCT. Cut sidewall cores from point 21 to 55. POOH and recovered cores. Made up tools, ran in and conducted logging run 7 VSI4-EDTC-LEH.							
02-01-2015	3180.00	Completed logging run 7. Pulled out of the hole and laid out logging tool string 7. Made up USIT-CBL-VDL-EDTC-CCL-LEH toolstring, ran in hole and conducted logging run 8. Pressure tested BOP's.							
03-01-2015 04-01-2015	3180.00 3180.00	2130mMDRT.	Completed pressure testing BOP's and well control equipment. Made up 6 3/4" clean out / 9 5/8" casing scraper assembly and ran in the hole to 2130mMDRT.  Ran in the hole with 6 3/4" clean out / 9 5/8" casing scraper assembly from 2130m to 3148m MDRT. Reamed and washed down to 3180mMDRT.						
05-01-2015	3180.00	Dropped pipe drift & pulled out to surface.  Cleared rig floor of BHA. Picked up cement head & torqued up	,						
06-01-2015	3180.00	ran 4 1/2" liner as per tally.  Picked up hanger assembly with running tools & made up to		·	·				
07-01-2015	3180.00	Set liner hanger & cemented liner at 3178mMDRT Racked back 5 1/2" drill pipe to mast.and laid out liner running	·	·					
08-01-2015	3180.00	206mMDRT.  Completed running in hole with 4 1/2" liner cleanout assembly	-	·	-				
09-01-2015	3180.00	1/2" bit and mud motor to 2969m MDRT  Completed drilling out cement to 3122.11m RT with mud mot		•					
10-01-2015	3180.00	Pressure tested 4 1/2" liner shoe to 5000psi. Pumped chemic down 5 1/2" drill pipe.		r, conducted inflow test. Displa	aced to 5% brine. POOH, laid				
11-01-2015	3180.00	Completed laying out 5 1/2" drill pipe and well bore cleanup E in. Ran in hole seal assembly & gauge mandrel.	BHA. Rigged up Weatherford CR	RT & associated equipment for	running in hole with 4 1/2" tie				
12-01-2015	3180.00	Ran in hole with 4 1/2" tie in string with gauge cable to 65.5m power tong to 1619mRT.	RT. Encountered backing up tu	bing while torquing up with ov	erdrive. Ran in on elevators &				
13-01-2015	3180.00	RIH with 4.5" tieback string c/w PDHG cable from 1619m to 2 & hanger assembly. Latched seal assembly and landed hang		R. Pressure tested seals. Space	ed out & picked up TRSCSSV				
14-01-2015	3180.00	Engaged tie down bolts. Pressure tested hanger seals, 4 1/2' Backed out landing joint. Installed BPV. ND BOP.	to 9 5/8" annulus and 4 1/2" tub	oing string. Ran inflow test on	TRSCSSV & on open tubing.				
15-01-2015	3180.00	Installed tubing head, terminated gauge cable & TRSCSSV li and secured well. Rig released at 17:00 hrs.	ne. Installed side outlet valves. F	Replaced BPV with TWCV. Ins	stalled frac sleeve. Capped				
		Key							
Breccia		Limestone	B Boundstone	c	arbonaceous				
Conglon	nerate	Dolomitic Limestone	G Grainstone		ituminous				
Conglon	.5.4.0	y Boloniao Emiosiono							
h: 1: 0 1/0	1.4	/ D   ''		1 ^ 1^	1141				








WOB: 3 klbs	3 rerun 17 1/2"				SILTSTONE: medium grey, argillaceous, arenaceous in parts interbedded with very fine SANDSTONE, moderately hard, blocky to sub		
TRQ: 4164 lbs.ft SPP: 1847 psi Flow: 1041 gpm RPM: 98	<b>\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\</b>				blocky, trace very fine lithics, trace carbonaceous inclusions.		
	3		200m		SANDSTONE: light grey, translucent, clear, very fine to predominantly fine grained, well sorted, sub angular to sub rounded, friable to		
	}				moderately hard, weak calcareous cement, rare siliceous cement, common light grey argillaceous matrix, interbedded with and		
	<b>*</b>				grading to SILTSTONE, minor carbonaceous fragments, poor to fair visual porosity, no fluorescence		208.800m 208.8m TVDBRT Inc: 0.26° Azi: 324.93°
	<b>}</b>				SANDSTONE: off white, translucent, light		A2I. 324.93
					grey, very fine to predominantly fine grained, moderately well sorted, sub angular to sub rounded, moderately hard, friable in parts,		
	<b>\\</b> \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	4			moderately strong siliceous cement, minor light grey argillaceous matrix, minor carbonaceous	111	
					inclusions, trace lithics, poor to fair visual porosity, no fluorescence		
	₹ <b>}</b>				SILTSTONE: light to medium brownish grey, light to medium grey, moderately hard, arenaceous grading to silty SANDSTONE,		No LWD data recorded from
	<b>* * * * * * * * * *</b>				trace carbonaceous specks, trace fine grained lithics.		224m to 233m
					SILTSTONE: medium brownish grey, medium		
			 250m	<u> </u>	grey, moderately hard, arenaceous grading to silty SANDSTONE, trace carbonaceous specks, trace fine grained lithics.		
	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	}			SANDSTONE: light to medium brownish grey,		
	\(\frac{1}{4}\)				off white, translucent, very fine to fine grained, moderately well sorted, sub angular to sub rounded, moderately hard, friable in parts,		
	[ ]				moderately strong siliceous and calcareous cement, common light grey argillaceous matrix, minor carbonaceous inclusions, trace	<b>\$</b>	
	<b>\</b>		 		lithics, poor visual porosity, no fluorescence SILTSTONE: medium brownish grey, medium		
	}				grey, moderately hard, argillaceous, arenaceous in parts, trace carbonaceous specks, trace fine grained lithics.		
					SANDSTONE: light grey, off white, light to		
WOB: 7 klbs TRQ: 6483 lbs.ft SPP: 2065 psi Flow: 1068 gpm	-		- · · - · · - · - · · - · · - · ·		medium brownish grey, translucent, very fine to fine grained, moderately well sorted, sub angular to sub rounded, moderately hard,	<u> </u>	
RPM: 97	4			<u> </u>	friable in parts, moderately strong calcareous and siliceous cement, minor very light grey argillaceous matrix, minor carbonaceous		
			- · · · - · · · - · · - · · · - · · · - · · - · · · - · · · - · ·		inclusions, trace lithics, poor visual porosity, no fluorescence		
			- · · -300m · · ·		SILTSTONE: medium to dark grey, medium to		
				<u> </u>	dark brownish grey, moderately hard, argillaceous, trace very finely arenaceous, sub blocky to sub fissile, blocky in part, trace	<b>\</b>	
	\(\frac{1}{2}\)				carbonaceous specks.		
						<b>}</b>	
		\ {			SANDSTONE: light grey, off white in parts, very fine to fine grained, well sorted, sub		
	<b>* * * *</b>	7	325m	<u> </u>	angular to sub rounded, silty, interbedded with arenaceous SILTSTONE, moderately hard, friable in parts, moderately strong calcareous		
	5				and siliceous cement, common light grey argillaceous matrix, common carbonaceous fragments and thin laminae, trace very fine		
					cream lithics, very poor to poor visual porosity, no fluorescence.		
	4		-		SILTSTONE: medium to dark grey, medium to		
	5 <b>5</b>				dark brownish grey, moderately hard, argillaceous, trace very finely arenaceous, subblocky to sub fissile, blocky in part, trace carbonaceous specks.		
	<u> </u>		350m		carbonaceous specks.		
			 		SILTSTONE: medium to dark grey, medium to dark brownish grey, moderately hard to hard,		
					dominantly argillaceous, trace very finely arenaceous, sub blocky to sub fissile, trace micromicaceous, trace disseminated pyrite.		
WOB: 9 klbs	1 5				SILTSTONE: dark grey, dark brownish grey,		
TRQ: 7975 lbs.ft SPP: 2057 psi Flow: 1058 gpm RPM: 99	28		375m		moderately hard to hard, argillaceous, trace very finely arenaceous, sub blocky to sub fissile, trace micromicaceous, trace		
IXF IVI. 99			 		disseminated pyrite, rare micro cream lithics .		
						<b>\</b>	
					SANDSTONE: light grey, light green, very fine to fine, well sorted, sub angular to sub		
I			<u> </u>		rounded, hard, strong calcareous and siliceous		



































## Dunk 1

	Bit Summary										
BHA No	Bit No	Status	Make/Type	Size	TFA	Jets	Depth In (mMDRT)	Progress (m)	Rotating Hours	Average ROP (m/hr)	Grading
1	1	new bit	NOV TFH519S-A2	17 1/2"	0.91	7x13	64.50	12.80	1.5	7.2	Not recorded
2	2	rerun	NOV TFH519S-A2	17 1/2"	0.91	7x13	77.30	107.60	6.5	34.8	Not recorded
3	2	rerun	NOV TFH519S-A2	17 1/2"	0.91	7x13	184.90	921.48	35.5	32.1	2-3-BT-S-X-0-LT-TD
4	3	new bit	NOV DSH516D	12 1/4"	0.77	7x12	1106.38	1223.62	80.82	15.1	1-2-DL-S-X-1-CT-TD
5	4	new bit	Smith MSi413EPX	6 3/4"	0.31	4x10	2330.00	540.00	57.1	9.5	2-2-CT-C-X-IN-ER-TD
6	5	new bit	Halliburton DBS FC3743A	6 3/4"	1.05	7x14	2870.00	27.00	18.0	1.5	1-1-WT-S-X-IN-ER-CP
7	6	new bit	Halliburton DBS FC3743A	6 3/4"	1.05	7x14	2897.00	27.27	4.6	5.9	0-0-ER-C-X-IN-RR-TD
8	7	new bit	Ulterra U613M	6 3/4"	0.46	5x11	2924.27	135.28	22.71	17.7	1-3-CT-G-X-IN-NO-BHA
9	8	new bit	Baker Hughes MX20GDX	6 3/4"	0.45	3x14	3059.55	120.45	33.6	3.6	1-1-WT-A-E-U-LN-TD

			Co	onventional Core	
No	Interval (m MDRT)	Cut (m)	Recovered (m)	Recovery (%)	Formation
1	2870.00 - 2897.00	27.00	26.66	98.7	Scotia Coal Cycle, Tinowon Formation
2	2897.00 - 2924.27	27.27	27.61	101.0	Tinowon Formation, Upper Tinowan Sandstone

	Wireline Logging Summary							
Suite/Run No	Hole/Casing Size	Suite	Date(s)	Interval (mMDRT)	Max Temp (°C)	Comments		
1.1	12 1/4"	PEX-HRLA-SSCAN-PPC-GPIT-SP	07/12/14 to 08/12/14	1099.00 - 2332.70	77.8	12 1/4" open hole		
1.1	12 1/4"	GR	07/12/14 to 08/12/14	20.00 - 2332.70	77.8	GR to surface inside 13 3/8" casing		
2.1	6 3/4"	FMI-SSCAN-PPC	28/12/2014	2328.06 - 3183.56	115.5			
2.2	6 3/4"	PEX-HRLA-APS- HNGS-SP-GR	28/12/2014	2328.06 - 3183.56	106.0			
2.3	6 3/4"	CMR-ECS	28/12/2014 to 29/12/2014	2328.06 - 3183.56	110.0			
2.4	6 3/4"	MDT	29/12/2014	2812.79 - 2933.31	110.0	Station log		
2.5	6 3/4"	MSCT	31/12/2014	3005.00 - 3133.75	104.5	Station log		
2.6	6 3/4"	MSCT	31/12/2014 to 01/01/2015	2384.85 - 3008.81	104.5	Station log		
2.7	6 3/4"	VSI4 (4 shuttle seismic)	01/01/2015	8.70 - 3117.97	110.0	Station log		
2.8	6 3/4"	USIT-CBL-CCL	02/01/2015	800.00 - 2328.00	102.0			

	Sidewall Cores					
Depth (mMDRT)	Recovery	Lithology/Comments				
3133.75	Good	Volcanics/Metamorphics: mottled red brown fine to medium quartz groundmass, some large green grey deformed phenocrysts/inclusions, trace dark mafic inclusions.				
3126.00	Good	Meta-SILTSTONE: light grey to light green grey, red brown, silty groundmass with light green grey granule to pebble TUFF fragments and lithics, with diffuse boundaries.				
3120.00	Poor	SANDSTONE: light grey, very fine to fine, occasional medium, re-crystallised in part, hard, very poor visible porosity, no fluorescence.				
3116.00	Good	SANDSTONE, light grey mottled with dark grey, very fine to fine, some re-crystallised with diffuse grain boundaries, moderately hard, very poor to tight visible porosity, no fluorescence.				

3112.78	Good	SANDSTONE: light grey, very fine to fine, occasional medium, recrystallised in part, occasional red brown silty inclusions, moderately hard to hard, very poor visible porosity, no fluorescence.
3093.00	Good	SANDSTONE: medium dark grey to dark grey, very fine to fine, trace medium grains, occasional light grey LIMESTONE micro laminations and inclusions, silty matrix, very poor visible porosity, trace patchy orange mineral fluorescence.
3085.33	Fair	CONGLOMERATE: medium to dark grey, fine to coarse, common granule to pebble white to light grey and green grey siliceous inclusions, occasional silty inclusions, hard, very poor visible porosity, trace patchy orange mineral fluorescence.
3083.00	Fair	SANDSTONE: brown grey, very fine to medium, occasional coarse grains, sub angular to sub round, trace lithics, occasional quartz overgrowths, hard, very poor visible porosity, trace patchy dull orange mineral fluorescence.
3081.43	Poor	SANDSTONE: very light grey, very fine to very coarse clear to translucent quartz grains, sub angular to sub round, poorly sorted, abundant white to light grey matrix, moderately hard, very poor visible porosity, trace fluorescence as above.
3076.47	Fair	SANDSTONE: light to medium grey, very fine to medium, common coarse to pebble sized inclusions, moderately sorted, trace dark grey lithics, moderately hard, poor to very poor visible porosity, trace dull orange patchy mineral fluorescence.
3075.00	Good	SANDSTONE: light to medium grey, very fine to medium, common coarse to pebble sized inclusions, silty matrix, moderately hard, very poor visible porosity, trace patchy dull orange mineral fluorescence.
3061.00	Good	SANDSTONE: medium dark grey, very fine to medium, trace coarse grains, sub angular to sub round, moderately sorted, silty matrix, occasional light grey to white lithics, silty matrix, moderately hard to hard, very poor visible porosity, patchy dull orange mineral fluorescence.
3046.48	Good	SANDSTONE: medium dark grey, very fine to fine, occasional medium to coarse grains, occasional lithics, silty matrix, moderately hard to hard, very poor visible porosity, trace patchy dull orange mineral fluorescence.
3043.10	Good	SILTSTONE: dark grey, dark brown grey, argillaceous, occasional LIMESTONE micro laminations, moderately hard to hard.
3037.50	None	No sample recovered
3025.00	Good	SILTSTONE: dark grey, dark brown grey, argillaceous, occasionally arenaceous in part, trace lithics, trace micro-mica, moderately hard to hard.
3021.58	Good	SILTSTONE: very dark grey, dark brown grey, argillaceous, trace micro-mica, hard.
3008.72	None	No sample recovered.
3007.76	None	No sample recovered.
3006.58	None	No sample recovered.
3005.00	Fair	Sample recovered (broken) from damaged core head of Run 5. SANDSTONE: light grey, fine to coarse, occasional granular grains, very poorly sorted, trace lithics, quartz overgrowths, moderately hard to hard, poor visible porosity, trace patchy dull orange mineral fluorescence.
3008.80	Good	SANDSTONE: light brown grey, fine to coarse, angular to sub round, poorly sorted, occasional argillaceous matrix, occasional broken grains, trace to occasional lithics, moderately hard, poor visible porosity, patchy dull orange mineral fluorescence.
3007.90	Fair	SANDSTONE: fine to coarse as above.
3006.80	Good	SANDSTONE: light brown grey, fine to very coarse, occasional granular grains, very poorly sorted, angular to sub round, occasional lithics, occasional matrix, poor visible porosity, trace patchy dull orange mineral fluorescence.
3005.20	Poor	Poor quality sample – rubble. SANDSTONE: as above.
3002.30	None	No sample recovered
2992.40	Good	SANDSTONE: medium dark grey brown grey, very fine to fine, trace medium grains, sub angular to sub round, silty matrix, very poor visible porosity, occasional patchy dull orange mineral fluorescence.
2975.90	Good	SANDSTONE with interbedded SILTSTONE. SANDSTONE: as described above. SILTSTONE: dark grey, argillaceous, slightly arenaceous, hard.
2970.90	Good	SANDSTONE: light to medium grey, very fine to fine, trace medium grains, sub angular to sub round, moderately sorted, trace matrix, trace lithics, moderately hard, very poor visible porosity, occasional patchy dull orange mineral fluorescence.
2967.80	Fair	SANDSTONE: light to medium grey, very fine to coarse, angular to sub round, poorly sorted, trace argillaceous matrix, occasional lithics, very rare pyrite, quartz overgrowths, very poor visible porosity, rare patchy dull orange mineral fluorescence.
2934.95	Good	SANDSTONE: medium to dark grey, fine to medium, occasional coarse, poorly sorted, angular to sub round, trace matrix, common altered feldspar, occasional quartz overgrowths, very poor visible porosity, no fluorescence.
2931.50	Good	SANDSTONE: medium dark grey, fine to medium, occasional coarse, angular to sub round, common to abundant altered feldspar (cream to light brown), trace matrix, occasional quartz overgrowths, very poor visible porosity, no fluorescence.
2920.70	Good	SANDSTONE: generally as described above – common to abundant altered feldspar, trace to occasional matrix, trace lithics, moderately hard to hard, very poor visible porosity, no fluorescence.
2912.30	Good	SANDSTONE: medium grey, light brown grey, fine to coarse, trace very coarse grains, trace argillaceous matrix, common lithics, common altered feldspar, occasional quartz overgrowths, moderately hard to hard, very poor visible porosity, no fluorescence.  SANDSTONE: medium grey, fine to medium, occasional coarse, sub angular to sub round, moderately sorted, common lithics, occasional altered feldspar (cream, pale brown),
		moderately hard, very poor visible porosity, no fluorescence.
2882.00	Good	SANDSTONE" medium grey, fine to medium, trace coarse grains, occasional lithics, trace to occasional altered feldspar, moderately hard to hard, very poor visible porosity, no fluorescence.
2868.00	None	No sample recovered
2864.30	Good	SILTSTONE: medium dark grey, abundant LIMESTONE fragments, fossil fragments.
2858.00	None	No sample recovered.
2848.00	Good	SANDSTONE with interbedded SILTSTONE separated by Tuffaceous laminae. SANDSTONE: medium dark grey, very fine to fine, grades to SILTSTONE, occasional lithics, rare carbonaceous specks, moderately hard, very poor visible porosity, no fluorescence. SILTSTONE: light grey, very finely arenaceous and grades to SANDSTONE. TUFF / CLAYSTONE?: pale brown firm.
2818.49	Good	SILTSTONE: light to medium grey, very finely arenaceous and grades to very fine SANDSTONE in part, occasional carbonaceous specks, micro-mica, moderately hard to hard.
2816.57	None	No sample recovered.
2813.00	Fair	SANDSTONE: light grey, very fine, grades to SILTSTONE, sub angular to sub round, occasional cark micro-specks, moderately hard, very poor visible porosity, no fluorescence.
2810.00	None	No sample recovered.
2796.11	None	No sample recovered.
2779.00	None	No sample recovered.
2790.07	None	No sample recovered.
2731.91	None	No sample recovered.
2719.45	None	No sample recovered.
2691.00	None	No sample recovered.
2669.12	Good	SANDSTONE: light to medium grey, green grey, very fine to medium, trace coarse grains, sub angular to sub round, trace carbonaceous specks, common to abundant lithics (green grey, grey, pale orange), trace altered feldspar, moderately hard, very poor visible porosity, no fluorescence.
2650.50	None	No sample recovered.
2582.99	None	No sample recovered.
2520.97	None	No sample recovered.
2384.85	Good	SANDSTONE: light grey, light brown grey, fine to very coarse, angular to sub round, occasional matrix, trace lithics, occasional altered feldspar, poor to fair visible porosity, no
	1	fluorescence.