Magnetic 1



Scale 1:500

Wellsite Lithology Log

Well Data

Well Name: Magnetic 1 Status: Exploration Area: Surat (8743) Basin: Bowen Basin ATP 645 Location:

UWI: 100000799278

Partners:

BNG (Surat) Pty Ltd 100%

TCL 1, Easternwell 106 Rigs:

27° 09' 37.2870" S Latitude: 149° 25' 10.2877" E Longitude: 09-04-2015 15:15 (TCL1) Spud Date:

TD Date: 13-05-2015 (Easternwell 106) 27-05-2015 19:00 (Easternwell 106)

Datum: 312.25m RT Elevation:

TD Formation: Timbury Hills Formation TD Depth: 3095.00m MDRT (driller)

3097.02m MDRT (logger)

Remarks:

Rig Release:

Geologists

Operations Geologist: Anthony Mountford Wellsite Geologist: Anthony Drake Wellsite Geologist: **Andrew Morris** Wellsite Geologist: Brendan Lacy Wellsite Geologist: John Pitman

Contractors


Drilling: TCL

Easternwell Energy Wireline Logging: Schlumberger Cementing: Halliburton Mud Engineering: Newpark Weatherford Mud Logging:

MWD: Pathfinder Coring: Halliburton

Hole and Casing					
Bit Size (inch)	Depth (m)	Casing Size (inch)	Shoe Depth (m)		
26"	69.11	20"	65.50		
17 1/2"	1203.00	13 3/8"	1200.00		
12 1/4"	2324.00	9 5/8"	2321.57		
8 1/2"	2327.00	N/A			
6 3/4"	3095.00	4 1/2"	3094.17		


Location Map




Depth (mMDRT)

Date

Details



Well Structure





Events and Remarks


	-	·
09-04-2015	27.71	TCL 1 move onto location. Rig up to spud. Make up 26" BHA. Spud well and drill ahead.
10-04-2015	69.11	Continue to drill ahead to section TD. Circulate hole clean. POOH to run 20" Casing. Lay out BHA.
11-04-2015	69.11	Rig up and run 20" casing. Cement in place.
12-04-2015	69.11	Rig down equipment. Cut 20" conductor at GL. Cement cellar floor. Move off location. Rig released.
13-04-2015	69.11	Easternwell rig 106 moving onto location.
14-04-2015	69.11	Rig 106 continue to rig move onto location and rig up.
15-04-2015	69.11	Rig 106 continue to rig move onto location and rig up.
16-04-2015	69.11	Rig 106 continue to rig move onto location and rig up.
17-04-2015	69.11	Rig 106 continue to rig move onto location and rig up.
18-04-2015	69.11	Rig 106 continue to rig move onto location and rig up.
19-04-2015	69.11	Rig 106 continue to rig move onto location and rig up.
20-04-2015	69.11	Rig 106 continue to rig move onto location and rig up.
21-04-2015	69.11	Rig 106 continue to rig move onto location and rig up.
22-04-2015	282.00	Commenced drilling Magnetic 1 at 04:00 hours on 22-04-2015 and drilled 17 1/2" surface hole.
23-04-2015	885.00	Drilled ahead 17 1/2" surface hole.
24-04-2015	1203.00	Drilled ahead 17 1/2" surface hole to 1203.00m MDRT. POOH and lay-down 17½" BHA. Rigged up to run 13 3/8" surface casing.
25-04-2015	1203.00	Picked up Weatherford casing gear and rigged up to run casing. Shimmed mast. RIH 13 3/8" surface casing. Rigged up Halliburton cement unit and cement surface casing. Waited on cement.
26-04-2015	1203.00	Continued to wait on cement. Slacked off and cut 13 3/8" casing. Installed wellhead. Nippled up BOP.
27-04-2015	1208.00	Pressure test BOP. Make up drill-pipe stands and rack back. Pick up 12 ¼" BHA and shallow test MWD. RIH with 12¼" BHA and drill out shoe track. Drill 5m of new formation. Circulate and condition mud.
28-04-2015	1832.00	Rigged up Halliburton and conducted LOT. Drilled ahead 12¼" hole.
29-04-2015	2324.00	Drilled ahead 12¼" hole to 2324m MDRT. Circulated hole clean.
30-04-2015	2324.00	Circulated hole. Conducted five std check-trip and RIH to bottom. POOH to csg shoe. Slipped drill line. RIH to TD, no fill. Circulated hole. POOH to 2240m. RIH to bottom. Circulated hole. POOH. Laid out LWD. Rigged up wireline loggers.
04 05 2045	2224.00	Continued rigging up wireling DIU legging tools. Commo with tools lost, fault find wireling computer system, DOOL wireling arring and avenued out


01-03-2013	2324.00	wireline truck with replacement. RIH wireline and o			ana swappea oa
02-05-2015	2324.00	Rigged up to run 9 5/8" casing. Shimmed mast to	realign. Damaged threads on float and interm		t joints. Picked up
03-05-2015	2324.00	spare float and intermediate joints and made up so Continued running in 9 5/8" casing to 2005m MDR	RT. Repaired drag-line securing rope. Continu		ned to bottom. Landed
04-05-2015	2327.00	and circulated casing. Rigged up Halliburton and c Completed jetting wellhead/BOP. Installed pack-or	ff and pressure tested same. Installed wear b	ushing. Slipped and cut line. Made u	p 8½" BHA and RIH.
05-05-2015	2375.00	Drilled out shoe-track and new hole to 2327.00m In Drilled 6 3/4" production hole.	MDRT. Circulated noie. Conducted XLOT. PC	OOH.	
06-05-2015	2876.00	Drilled 6 3/4" production hole.			
07-05-2015	2936.60	Drilled 6 3/4" production hole to core point. Condu	ucted wiper trip. POOH to surface. Made up 6	3/4" coring BHA.	
08-05-2015	2972.60	Ran in hole 6 3/4" coring BHA for Core Run 1 to b	ottom. Tagged bottom. Cored 6 3/4" hole. Cir	culated BU. POOH.	
09-05-2015	2976.00	POOH to surface and recovered core 1. Made up	coring BHA 2 and ran in the hole to bottom. C	Cored 6 3/4" hole.	
10-05-2015	3008.60	Cored 6 3/4" hole to 3008.60m MDRT. POOH.			
11-05-2015	3008.60	Continued to pull out of the hole with Core 2 to sur assembly and test BOPs.	, ,	·	•
12-05-2015 13-05-2015	3020.00 3095.00	Replaced seals completed reruns of pressure test 3/4" hole from 3008.6m MDRT. Drilled 6 3/4" hole to 3095.00m MDRT (TD). Circu	·		
		to 2560m MDRT.			
14-05-2015	3095.00	Ran in the hole from 2560m MDRT to 3055m MDR	RT. Circulated hole clean. Flow checked & PC	OOH to surface. Rigged up wireline a	nd conducted Suite 2.
15-05-2015	3095.00	Continue with wireline logging Suite 2.			
16-05-2015	3095.00	Continue with wireline logging Suite 2.	N. I		
17-05-2015	3095.00	Complete wireline logging Suite 2. Rigged down S	·	• •	
18-05-2015 19-05-2015	3095.00 3095.00	Continued to RIH. Washed down from 3070m MD POOH. Laid out 4" DP, BHA and clean out assem Ran 4 1/2" liner 869m MDRT. Picked up WFT low	bly. Rigged up WFT TRS. Ran 4 1/2" liner		
20-05-2015	3095.00	bottom at 3095m MDRT. Made up WFT cement he Conducted cement job. Rigged down cement hear	ead. Set 4 1/2" liner.		
21-05-2015	3095.00	tools and laid down. Pulled wear bushing & jetted RIH 2 3/8" tubing from 100m MDRT to 819m MDR	BOP. Pressure tested. RIH CTD motor on 23	3/8" tubing.	
22-05-2015	3095.00	to 3042.02m MDRT. Dressed top of PBR's. Dropp Pumped well bore clean up chemical train as per p	ed seating ball. Circulated & landed ball.		
23-05-2015	3095.00	brine. Flow checked & POOH laying out 5 1/2" dri Broke down & laid out wellbore clean up assembly	• •	VFD CTD motor. Rigged down 2 3/8"	handling equipment.
	0000.00	Rigged up Weatherford TRS and PDHG. Ran 4 1/		0e.eggea ae 0,e	g equipe
24-05-2015	3095.00	Rigged up Halliburton casing string and tested. Ri	gged up wireline and commenced Suite 3.		
25-05-2015	3095.00	Continue with wireline logging.			
26-05-2015	3095.00	Continued with suite 3. Completed logging and rig BOP's.	g down wireline. Back out and laid out landing	joint/running tool. Installed BPV with	GE. Nippled down
27-05-2015	3095.00	Nipple down BOP and installed suspension cap. F			
			Key		
Brecci	ia	Limestone	B Boundstone	Carbonace	eous
Congle	omerate	Dolomitic Limestone	G Grainstone	→ Bituminous	S
10000					
Sand/	Sandstone	Dolomite	M Mudstone	Oolitic	
Silt\Sil	Itstone	Calcareous Dolomite	P Packstone	I Chalky	
		V			
Clay/C	Claystone	Chert	W Wackestone	♣ Glauconiti	C
⊥ [⊥] ⊥ Marl		^ ^ Anhydrite	- · · Silty	Mic Micaceous	3
Shale		Halite	— — Argillaceous	Pyritic	
V ∨ Tuff		Polyhalite	→ Calcareous	✓ Spicules	
T dil		•	Galloaroodo	, opicales	
Volcar	nics	Coal/Lignite	→ Dolomitic	∂ Fossilifere	ous
		No Sample			
		INO Sample	/ Brecciated		
β Mud/Casing	Drilling	Cuttings ਨੇ Lithology ਨਿ Lithology ਹੈ Interpreted	Lithological	Gas Data	Remarks
Mud/Casing		Lithology 🔓 Interpreted ଠ୍ର	Descriptions		
	Parameters			1	
	Parameters	Still grant St			
	Parameters	Cuttings Lithology Swods		Doop Posictivity	
	Parameters	Stratign		Deep Resistivity 0.2 (ohm.m) 2000	
	Gamma - GRO	Strati		Medium Resistivity	
0_	Gamma - GRC (API) Units	Strati		Medium Resistivity 0.2 (ohm.m) 2000	
0	Gamma - GRC (API) Units ROP	Strati		Medium Resistivity	
0 25 N/A Shoe @ mMDRT	Gamma - GRC (API) Units ROP	Strati		Medium Resistivity 0.2 (ohm.m) 2000 Shallow Resistivity	
N/A Shoe @	Gamma - GRC (API) Units ROP 60 m/hr WOB	Strati		Medium Resistivity 0.2 (ohm.m) 2000 Shallow Resistivity 0.2 (ohm.m) 2000 Total Gas	
N/A Shoe @	Gamma - GRC (API) Units ROP 60 m/hr WOB	Formation Strati		Medium Resistivity 0.2 (ohm.m) 2000 Shallow Resistivity 0.2 (ohm.m) 2000 Total Gas	
N/A Shoe @	Gamma - GRC (API) Units ROP 60 m/hr WOB	20 05 0 05 00 000 000 000 000 000 000 00		Medium Resistivity 0.2 (ohm.m) 2000 Shallow Resistivity 0.2 (ohm.m) 2000 Total Gas	
N/A Shoe @	Gamma - GRC (API) Units ROP 60 m/hr WOB	20 05 0 05 00 000 000 000 000 000 000 00		Medium Resistivity 0.2 (ohm.m) 2000 Shallow Resistivity 0.2 (ohm.m) 2000 Total Gas	
N/A Shoe @ 0 mMDRT	Gamma - GRC (API) Units ROP m/hr WOB (klbs)	20 05 0 05 00 000 000 000 000 000 000 00		Medium Resistivity 0.2 (ohm.m) 2000 Shallow Resistivity 0.2 (ohm.m) 2000 Total Gas	
N/A Shoe @ 0 mMDRT	Gamma - GRC (API) Units ROP 60 m/hr WOB	20 05 0 05 00 000 000 000 000 000 000 00		Medium Resistivity 0.2 (ohm.m) 2000 Shallow Resistivity 0.2 (ohm.m) 2000 Total Gas	


25m









































	Bit Summary										
BHA No	Bit No	Status	Make/Type	Size	TFA	Jets	Depth In (mMDRT)	Progress (m)	Rotating Hours	Average ROP (m/hr)	Grading
1	1	new bit	Baker Hughes	26"			8.71	60.40	11.75	5.1	1-1-WT-A-0-0-WT-TD
1	1	new bit	Baker Hughes	17 1/2"	1.17	9x13	65.50	1133.89	37.6	30.3	0-1-CT-S-X-I-NO-TD
2	2	new bit	Baker Hughes	12 1/4"	0.97	4x14,2x13,1x12	1203.00	1121.00	32.1	34.9	1-3-CT-G-X-I-DL-TD
3	3	new bit	Varel	8 1/2"	0.52	3x15	2324.00	3.00	2.0	1.5	0-0-NO-A-1-0-N0-BHA
4	4	new bit	Smith	6 3/4"	0.44	4x12	2327.00	609.60	25.7	23.7	1-5-BT-S-X-0-CT-CP
5	5	new bit	Corpro	6 3/4"		-	2936.60	36.00	6.3	5.7	1-1-CT-N-X-I-PN-CP
6	6	new bit	Corpro	6 3/4"		-	2972.60	36.00	17.6	2.0	1-1-ER-N-X-I-PN-TD
7	7	new bit	Smith	6 3/4"	0.39	4x12	3008.60	86.40	20.1	4.3	1-1-NO-A-E-0-NO-TD

			Co	onventional Core	
No	Interval (m MDRT)	Cut (m)	Recovered (m)	Recovery (%)	Formation
1	2936.60 - 2972.60	36.00	36.41	101.0	Lorelle Sandstone
2	2972.60 - 3008.60	36.00	36.00	100.0	Lorelle Sandstone

Wireline Logging Summary

Suite/Run No	Hole/Casing Size	Suite	Date(s)	Interval (mMDRT)	Max Temp (°C)	Comments
1.1	12 1/4"	PEX-HRLA-SSCAN-PPC	01-05-2015	20.00 - 2326.60	88.2	Gamma only to surface
2.1	6 3/4"	FMI-SSCAN-PPC	14-05-2015	2321.31 - 3097.02	103.7	
2.2	6 3/4"	PEX-HRLA-HNGS-APS	15-05-2015	2321.31 - 3097.02	105.55	
2.3	6 3/4"	CMR-ECS	15-05-2015	2321.31 - 3097.02	110.00	
2.4	6 3/4"	MSCT	15-05-2015 to 16-05-2015	2732.80 - 3040.70	110	
2.5	6 3/4"	VSP	16-05-2015 to 17-05-2015	1198.00 - 3095.00	104.55	check shots to 32.42m MDRT
2.6	6 3/4"	CBL-VDL-CCL	17-05-2015	900.00 - 2321.31	82.2	
3.1	4 1/2"	JB-CCL	25-05-2015	2200.00 - 3039.77		Cased hole log
3.2	4 1/2"	SCMT-PBMS	25-05-2015	2150.00 - 3042.51		Cased hole log
3.3	4 1/2"	JB-CCL	25-05-2015	2000.00 - 3038.00		Cased hole log
3.4	4 1/2"	RST-PBMS	26-05-2015	2700.00 - 3038.00		Cased hole log
3.5	4 1/2"	TBDS	26-05-2015	2150.00 - 3040.00		Cased hole log

Depth (mMDRT)	Recovery	Lithology/Comments
3040.70	Good	META-SANDSTONE: light grev to light greenish grev, re-crystalized guartz, hard to very hard, strong siliceous cement, trace to minor siliceous matrix, trace medium to come the company of
3036.00	Good	lithics, trace pyrite, very poor to nil visible porosity, no fluorescence. META-SANDSTONE: light grey to light greenish grey, re-crystalized quartz, hard to very hard, strong siliceous cement, trace to minor siliceous matrix, trace medium lithing.
		pyrite, very poor to nil visible porosity, no fluorescence.
3031.90	Good	META-SANDSTONE: light grey to light greenish grey, re-crystalized quartz, hard to very hard, strong siliceous cement, trace to minor siliceous matrix, trace medium lithi pyrite, very poor to nil visible porosity, no fluorescence.
3020.50	Good	META-SANDSTONE: light grey to light greenish grey, re-crystalized quartz, hard to very hard, strong siliceous cement, trace to minor siliceous matrix, trace META-SILTs sub rounded to rounded very coarse to pebble, trace medium lithics, rare pyrite, very poor to nil visible porosity, no fluorescence. Fractured.
3017.30	Good	META-SANDSTONE: light grey to light greenish grey, re-crystalized sub angular quartz, hard to very hard, strong siliceous cement, trace to minor siliceous matrix, trace minor META-SILTSTONE sub rounded to sub angular very coarse to pebble, rare medium lithics, very poor to nil visible porosity, no fluorescence.
3013.30	Good	META-SANDSTONE: light grey to light greenish grey, re-crystalized sub angular quartz, hard to very hard, strong siliceous cement, trace to minor siliceous/argillaceous minor to common SILTSTONE sub rounded to sub angular very coarse to pebble, trace pyrite, rare fine to coarse lithics, very poor to nil visible porosity, no fluorescence
3011.30	Good	CONGLOMERATIC SANDSTONE: very light grey to light greenish grey, commonly re-crystalized sub angular quartz grading to META-SANDSTONE, hard to very hard, siliceous cement, trace to minor siliceous/argillaceous matrix, minor medium grey SILTSTONE sub rounded to angular very coarse to pebble, minor to common medium coarse greyish grey lithics, very poor to nil visible porosity, no fluorescence.
2994.70	Good	CONGLOMERATIC SANDSTONE: very light grey to light greenish grey, commonly re-crystalized sub angular quartz grading to META-SANDSTONE, hard to very hard, siliceous cement, trace to minor siliceous/argillaceous matrix, minor medium grey SILTSTONE sub rounded to angular very coarse to pebble, common medium to pebbl greyish grey lithics, very poor to nil visible porosity, no fluorescence.
2950.10	Good	SANDSTONE: very light grey to light brownish grey, very fine to very coarse clear to translucent quartz grains, sub angular to sub rounded, hard to very hard, poorly sort strong siliceous cement, common very light grey to light grey argillaceous matrix, trace medium grey lithics, poor to very poor visible porosity, no fluorescence.
2940.80	Good	SANDSTONE: very light grey to light brownish grey, very fine to coarse predominantly transparent to translucent quartz grains, sub angular to sub rounded, hard, poorly moderately sorted, moderately strong siliceous cement, common very light grey argillaceous matrix, trace medium grey to dark grey medium to coarse lithics, poor to very visible porosity, no fluorescence.
2933.80	Good	SANDSTONE: medium light grey to medium grey, very fine to medium grained, occasionally coarse quartz, sub angular to sub rounded, hard, moderately sorted, mode strong siliceous cement, common medium grey argillaceous matrix, trace medium grey to dark grey lithics, poor to very poor visible porosity, no fluorescence.
2931.40	Good	SANDSTONE: medium light grey to medium grey, very fine to medium grained, trace coarse, sub angular to sub rounded, hard, moderately to poorly sorted, moderately siliceous cement, trace light brownish grey argillaceous matrix, trace medium grey to dark grey lithics, poor to very poor visible porosity, no fluorescence.
2927.00	Good	SANDSTONE: very light grey to light brownish grey, very fine to very coarse grained, sub angular to sub rounded, hard, moderately to poorly sorted, moderately strong siliceous cement, trace very light grey to very light brownish grey argillaceous matrix, trace medium grey to dark grey lithics, trace carbonaceous fragments, poor visible porosity, no fluorescence.
2926.40	Good	ARENACEOUS SILTSTONE: medium grey to medium dark grey, arenaceous grading to very fine SANDSTONE, trace lithics, trace mica, trace pyrite, moderately hard to
2914.80	Good	ARENACEOUS SILTSTONE: medium grey to medium dark grey, arenaceous grading to very fine SANDSTONE, trace lithics, trace mica, trace pyrite, moderately hard to
2892.70	Good	SANDSTONE: very light grey to light greenish grey, transparent to translucent, mottled, fine to granule, sub rounded to sub angular, hard, poorly sorted, moderately stro cement, minor very light grey to very light brownish grey argillaceous matrix, trace lithics, poor to fair visible porosity, no fluorescence.
2892.20	Good	CONGLOMERATIC SANDSTONE: light grey to medium grey, very fine to medium grained, common granules and pebbles, poorly sorted, hard, moderately strong ceme argillaceous in parts, very poor visible porosity, no fluorescence.
2866.50	Good	SANDSTONE: very light grey to light brownish grey, very fine to very coarse grained, rare granule, sub angular to sub rounded, moderately hard to hard, moderately to passive sorted, moderately strong cement, minor very light grey to very light brownish grey argillaceous matrix, trace lithics, poor to fair visible porosity, trace speckled dull yellow fluorescence.
2864.00	Good	SANDSTONE: very light grey to light brownish grey, very fine to very coarse grained, rare granule, sub angular to sub rounded, moderately hard, moderately to poorly so moderately strong cement, minor very light grey to very light brownish grey argillaceous matrix, trace lithics, poor to fair visible porosity, trace speckled very dull yellow fluorescence.
2816.60	Good	SANDSTONE: light grey to light brownish grey, very fine to medium grained, sub angular to sub rounded, moderately hard, moderately to well sorted, moderately strong cement, trace light grey argillaceous matrix, trace lithics, poor to fair visible porosity, minor speckled dull yellow fluorescence. SILTSTONE: medium grey to medium dark grey, slightly arenaceous grading to very fine SANDSTONE, moderately hard to hard.
2808.20	Good	SILTSTONE: medium grey to medium dark grey, arenaceous, minor dark grey argillaceous clasts, moderately hard.
2801.30	Good	SANDSTONE: light grey to light brownish grey, very fine to medium grained, sub angular to sub rounded, moderately hard, moderately to well sorted, moderately strong cement, trace light grey argillaceous matrix, trace lithics, poor to fair visible porosity, no fluorescence.
2800.20	Good	SANDSTONE: light grey to light brownish grey, very fine to medium grained, sub angular to sub rounded, moderately hard, moderately to well sorted, moderately strong cement, minor light brownish grey argillaceous matrix, trace lithics, poor to fair visible porosity, no fluorescence.
2794.10	Good	SANDSTONE: very light grey to very light brownish grey, very fine to medium grained, sub angular to sub rounded, moderately hard, well sorted, moderately strong cem minor very light brownish grey argillaceous matrix, trace lithics, poor to fair visible porosity, no fluorescence.
2792.70	Good	SILTSTONE: medium grey to medium dark grey, arenaceous in parts, common calcareous fragments, fossiliferous, moderately hard to hard.
2790.80	Good	SILTSTONE: medium grey to medium dark grey, arenaceous, common calcareous fragments, fossiliferous, moderately hard to hard.
2748.00	Good	SILTSTONE: light grey, light brownish grey, siliceous, lutaceous in parts, laminated, carbonaceous fracture infill, trace carbonaceous specks, hard.
2740.40	None	Not recovered
2734.60	Good	SANDSTONE: light grey to light brownish grey, very fine to medium grained, sub angular to sub rounded, moderately hard to hard, moderately to well sorted, moderately
	I	cement, trace very light grey argillaceous matrix, trace pyrite, laminated in parts, poor to fair visible porosity, no fluorescence.